



COMPANY QUALITY PROFILE
In Business since 1936

LOCATION ADDRESS: Corporate Office		Street: 10634 Shoemaker Avenue	City: Santa Fe Springs	State: CA	Country: USA	Zip: 90670-4038
Mailing address: P.O. BOX 2220 Santa Fe Springs, CA 90670-2220 USA				Web site Address: www.ejbco.com		
Building: Owned	Total Floor space: 78,000 sq. ft.	Warehouse: 55,000 sq. ft.	Manufacturing: 15,000 sq. ft.			
Total employees: 58	Sales/Purchasing: 22	Quality: 1	Manufacturing: 25	Administration: 10		
QUALITY PROGRAM:		ISO 9001:2008 + AS 9120:2002	Expiration Date: February 17, 2014	Registration Number: 0054630	Cage Code: 63G04 (8/2011)	
Company contacts	President/CEO	Sales Manager	Controller/HR	Quality Assurance Manager	General Manager	
Name	Robert Brookes Jr.	Lindsey Fisher	Ed Sarell	Ken Winiacki	Jon Quesenberry	
Phone	562-968-2100	562-968-2100	562-968-2100	562-968-2100	562-968-2100	
Fax	562-968-2110	562-968-2110	562-968-2110	562-968-2110	562-968-2110	
E-Mail		lfisher@ejbco.com	esarell@ejbco.com	kwiniecki@ejbco.com		
		Reports to the President	Reports to the President	Reports to the President	Reports to the President	

LOCATION ADDRESS: Fremont Branch		Street: 4121 Business Center Drive	City: Fremont	State: CA	Country: USA	Zip: 94538
Building: Owned	Total Floor space: 13,000 sq. ft.	Warehouse: 9,000 sq. ft.	Manufacturing: 2,000 sq. ft.			
QUALITY PROGRAM:		No Formal Quality Program	All Documents are stored at:	Santa Fe Springs, CA		
Company contacts	Branch Manager					
Name	Annie Vieau					
Phone	510-770-1500					
Fax	510-770-1510					
E-Mail	avieau@ejbco.com					
	Reports to the President					

Type of Business: Value Added Supplier of Raw Copper Alloy Materials and Engineered Plastics

Calibration Inspection to: ANSI-NCSL Z540.3-2006, ISO 10012-1

Hours of operation: Monday through Friday, 6am – 5pm Pacific Standard Time. Saturday if required

Manufacturing capabilities (not limited to):

Slitting; Thickness =.001 - .096, **Width** = .054 – 26”, Standard rule for width is 10 times the thickness.

Cut to Length Sheet; Thickness =.002 - .063, **Length** =2” – 144”, **Width** =1/2” – 24.5”,

Cut to length Bar Stock; 1/8” to 10” Diameter,

Tension Leveling; Thickness =.003 - .062, **Width** =1/4” – 4”,

Traverse wind; Thickness = .007 - .050, **Width** =1/4” – 2”, up to 4,000 lbs.,

Edge rolled to reduce burr; Thickness =.016 - .065, **Width** =1/4” – 24.5”,

Edge Skived to remove burr; (Hard Temper or Greater) **Thickness** =.008 - .032, **Width** = 1/4” – 2”.

All Customer #2 audits must be scheduled and approved before the audit.

Form filled out by: Ken Winiacki

Title: Quality Assurance Manager

Date: March 3, 2011